

Fine Fissured

Mineral Fiber Ceilings

LOW
VOC

\$\$\$\$

LEED® v4

LEED® v4

● MR: Environmental Product Declarations (EPDs)

● MR: Sourcing Raw Materials

● MR: Material Ingredients (HPDs)

● IEQ: Daylight

● IEQ: Low-Emitting Materials

● IEQ: Prereq. Min. Acoustic Performance (Schools)

● IEQ: Acoustic Performance

● MR: PBT Source Reduction (Healthcare)

● IEQ: Interior Lighting

● EA: Prereq. Min. Energy Performance

● EA: Optimize Energy Performance

● Recycled Content
CLASS A Pre: **28%** Post: **2%**
PROTECTONE® Pre: **37%** Post: **1%**

TOOLS

Visit CertainTeed.com/Ceilings
Download HPDs and EPDs
LEED® Information / BIM Objects
3-Part Specs / Data Pages



In addition to traditional white, you can make an impact with one of our 5 standard colors for item numbers HHF-154, HHF-157, HHF-197



Beige Breeze

Blondewood

Silver Lining

Wet Clay

White Wash

FEATURES & BENEFITS

- 100% non-directional pattern
- Available in fire-rated (Protectone®) versions
- Variety of edge detail options and panel sizes
- High humidity and sag resistant
- Third-party verified Environmental Product Declaration (EPD) available for this product
- Health Product Declaration (HPD) available for this product

APPLICATIONS

- Schools
- Libraries
- Retail / Department Stores
- Offices
- Other Commercial Buildings / Space Applications



Carbon Footprint Reduction
Rapidly Renewable Resource Content
Recycled Content



EPD Available



HPD Available

AVAILABLE EDGE DETAILS



Trim
15/16 Grid



Reveal
Beveled
15/16 Grid



Narrow Reveal
Corner Bevel
9/16 Grid



Narrow Reveal
Corner Bevel
9/16 Grid Bolt Slot

Color-coordinated suspension systems available



Fine Fissured Reveal (White) (HHF-154)

ATTRIBUTES

	DIMENSIONS INCHES	EDGE DETAIL	UL CLASSIFIED NRC	CLASSIFIED CAC	EPD AVAILABLE	HPD AVAILABLE	SAG RESISTANT	MOLD RESISTANT	LR	WASHABLE	FIRE CLASS (ASTM E1264)	EMISSION COMPLIANT	RECYCLED CONTENT
FINE FISSURED													
HHF-157	24 x 24 x 5/8	Trim	0.55	33	Yes	Yes	Yes	BioShield	0.84	—	Class A	Certified	30%
PFF-157	24 x 24 x 5/8	Trim	0.55	35	Yes	Yes	Yes	BioShield	0.84	—	Protectone*	Certified	38%
HHF-154	24 x 24 x 5/8	Reveal	0.55	33	Yes	Yes	Yes	BioShield	0.84	—	Class A	Certified	30%
PFF-154	24 x 24 x 5/8	Reveal	0.55	35	Yes	Yes	Yes	BioShield	0.84	—	Protectone*	Certified	38%
HHF-150	24 x 24 x 5/8	Narrow Reveal	0.55	35	Yes	Yes	Yes	BioShield	0.84	—	Class A	Certified	30%
HHF-197	24 x 48 x 5/8	Trim	0.55	35	Yes	Yes	Yes	BioShield	0.84	—	Class A	Certified	30%
PFF-197	24 x 48 x 5/8	Trim	0.55	40	Yes	Yes	Yes	BioShield	0.84	—	Protectone*	Certified	38%
HHF-194	24 x 48 x 5/8	Reveal	0.55	35	Yes	Yes	Yes	BioShield	0.84	—	Class A	Certified	30%
HHF-2067	20 x 60 x 5/8	Trim	0.55	35	Yes	Yes	Yes	BioShield	0.84	—	Class A	Certified	30%
HHF-177	24 x 60 x 5/8	Trim	0.55	35	Yes	Yes	Yes	BioShield	0.84	—	Class A	Certified	30%
FINE FISSURED - METRIC													
HHF-2067M	500 x 1500 x 15	Trim	0.60	35	Yes	Yes	Yes	BioShield	0.84	—	Class A	Certified	30%

* Protectone*: A fire-resistive ceiling when used in applicable UL assemblies.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL

Mineral Fiber

ASTM E1264 CLASSIFICATION

Type III, Form 2, Pattern C D

FIRE CLASS (ASTM E1264)

Tested according to ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010.

MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold and mildew resistance.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

15-Year Limited System Warranty

INSTALLATION CONSIDERATION

Colored ceilings are dye-lotted and should not be mixed.

Technical Support | certainteed.com/ceilings 800-233-8990

© 05/18 CertainTeed Corporation

CertainTeed
SAINT-GOBAIN
Ceilings